

## 2020 LOWER-COST ENVIRONMENTAL DATALOGGER QUICK COMPARISON CHART

Model, and Manufacturer	Accuracy	Wireless/Bluetooth/USB	Unit Price*‡	Software	Notes
EasyLog EL-USB-2 Lascar www.lascarelectronics.com	T:±0.55°C from 5 to 60°C RH:±2.25% from 20 to 80%	USB (direct to computer)	\$74.99	EasyLog Free download	No alarm function
LogTag HAXO-8 Temp and Humidity Recorder www.techinstrument.com	T: ±0.5°C from 0 to 50°C RH: ±3% from 20-80% (at 25°C)	USB via docking station (\$49)	\$79	LogTag Analyzer Free download	Provides alert function
HOBO Low Energy Temp/RH Data Logger MX1101 Onset www.onsetcomp.com	T: ±0.21°C from 0 to 50°C RH: ±2.0% from 20-80% (at 25°C)	Bluetooth	\$135	HOBOmobile App for iOS/Android Free download	Direct data access within 100-foot range
HOBO Temp/RH/Light/External Data Logger U12-012 Onset www.onsetcomp.com	T: ±0.35°C from 0 to 50°C RH: ±2.5% from 10-90% (at 25°C)	USB cable (not included in unit price, but available with HOBOware Pro package)	\$140	HOBOware Free download  HOBOware Pro \$75 download	No alarm function, measures light intensity
HOBO 3.5% Temp/RH Data Logger UX100-003 Onset www.onsetcomp.com	T: ±0.21°C from 0 to 50°C RH: ±3.5% from 25-85% (at 25°C)	USB cable (not included in unit price, but available with HOBOware Pro package)	\$89	HOBOware Free download HOBOware Pro \$75 download	Visual alarm thresholds
log-EZ RTR-322 TandD www.tandd.com	T: ±1°C from 0 to 50°C RH: ±6% from 15-90% (at 25°C)	Wireless between logger and Dongle Data Collector (extra USB \$50)	\$109	log-EZ Free download	No alarm function, fixed sampling interval 10 minutes

Model, and Manufacturer	Accuracy	Wireless/Bluetooth/USB	Unit Price*‡	Software	Notes
Conserv SCS-1 Sensor Conserv Solutions <a href="https://start.conserv.io/">https://start.conserv.io/</a>	T: ±0.2°C from -40-85°C RH: ±2% from 0-100%	Remote wireless monitoring, no Wi-fi needed	\$220	No software, just web and mobile app	Real time alerts. Also records light and vibrations
Portable Temperature/Humidity Data Logger with USB Interface OM-141 Omega www.omega.com	T: ±1.0°C from -10-40°C RH: ±3% from 20-80%	USB (direct to computer)	\$70.98	ELusb Software Included on disc	Alarm included in software
Tinytag Ultra 2 TGU 4500 Gemini www.geminidataloggers.com	T: ±0.7°C from -25-85°C RH: ±3.0% from 0-95% (at 25°C)	3-pin plug to USB cable (\$39), bundle with software for \$29 discount.	\$160	Tinytag Explorer \$78 on disc. Bundle with cable for \$29 discount	2 fully programmable alarms
Track-It RH/Temp Data Logger 5396-0203 Monarch Instrument www.monarchinstrument.com	T: ±0.5°C from 0-60°C RH: ±3% from 20-80%	USB (direct to computer)	\$79	Track-It and Track-It Transport Android App Free download	2 alarms, long life battery available for \$30 more
Track-It RH/Temp Data Logger with Display 5396-0201 Monarch Instrument www.monarchinstrument.com	T: ±0.5°C from 0-60°C RH: ±3% from 20-80%	USB (direct to computer)	\$119	Track-It and Track-It Transport Android App Free download	2 alarms, long life battery available for \$30 more

## Note: This chart is for reference only. CCAHA does not endorse or recommend any of the above models.

## **Further reading**

National Park Service, Comparing Temperature and Relative Humidity Dataloggers for Museum Monitoring.

www.nps.gov/museum/publications/conserveogram/03-03.pdf

Relative Humidity and Temperature Pattern Book, Museums & Galleries Commission.

 $\frac{https://326gtd123dbk1xdkdm489u1q-wpengine.netdna-ssl.com/wp-content/uploads/2017/03/Museums-Galleries-Commission-Relative-Humidity-and-Temperature-Pattern-Book-2000.pdf}\\$ 

<sup>\*</sup>Price in US Dollars before shipping and tax as of August 2020 from online retailers.

<sup>‡</sup>All dataloggers should be calibrated routinely per manufacturer's instructions, which may incur an additional fee. See manufacturer's website for information.